



Email: sales@blakesmarine.com.au Website: https://www.blakesmarine.com.au 1 Railway Road North Mulgrave NSW 2756



Suzuki DF175A

POA



Specifications

Boat Details

Price POA Boat Brand Suzuki
Model DF175A Length 0.00

Year 2020 Category Boat Engines and Outboards

Hull StyleHull TypePower TypeStock NumberDF175A

ConditionNewStateNew South WalesSuburbMULGRAVEEngine MakeSuzuki

Finance Available

Terms & Condition

This weekly repayment estimate is provided by Stratton Finance Pty Ltd (Australian Credit Licence No. 364340) ("Stratton"). Stratton is a finance broker. This repayment is calculated with an interest rate of % p.a. over a term of months. The interest rate is indicative of the rates on offer through Stratton's lending panel. The repayment estimate applies to the price shown. The price shown may not include other additional costs such as stamp duty, government fees and other charges payable in relation to the item. This estimate should be used for information purposes only and is not an offer of finance on particular terms. Credit fees, service fees and charges may apply. Credit to approved applicants only. A quote, details of all fees and charges may be obtained by contacting Stratton via stratton.com.au or calling 1300 955 600.



Phone: 02 4577 6699 Email: sales@blakesmarine.com.au

Website: https://www.blakesmarine.com.au

1 Railway Road North Mulgrave NSW 2756

From \$ p/w^. Please call 1300 787 288 for more information.

Description

DF175A

Features

Suzuki easy start system $\square\square\square$ Standard

Multi-point sequential electronic fuel injection □□□Standard

Variable valve timing □□□Standard

Offset driveshaft [[]]Standard

Over-rev. limiter [[]]Standard

Low oil pressure caution □□□Standard

Speedometer pickup on gear case □□□Standard

Suzuki anti-corrosion system [][]Standard

Suzuki Lean Burn Control system DDDStandard

16-valve DOHC (dual overhead cam) design □□□Standard

Power trim & tilt □□□Standard

Variable valve timing system □□□Standard

Suzuki troll mode system
□□□Optional

Quiet operation [[]]Standard

Suzuki water detecting system □□□Standard

Specifications

Shaft length $\square\square\square$ L: 508mm (20") | X: 635mm (25")

Fuel delivery system □□□Multi-point sequential electronic fuel injection

Maximum output □□□129.0kW

Full throttle operating range □□□5,500-6,100rpm

Steering DRemote

Oil pan capacity □□□8.0 litres

Ignition system $\hfill\Box\Box Fully\mbox{-transistorised}$

Alternator DDD12V 44A

Trim method $\square\square\square$ Power trim & tilt

Gear ratio DDD2.50:1

Gear shift □□□F-N-R (Drive by Wire)

Exhaust [] Through prop hub exhaust

Propeller selection (pitch) [17"-27" (s/s)

Fuel □□□minimum 91 (RON) octane

Warranty □□□5 years for recreational use

Engine Details

Engine Make Suzuki
Horse Power 175
Drive Type 8