





Website: https://www.blakesmarine.com.au 1 Railway Road North Mulgrave NSW 2756





Suzuki DF300AP

POA







DF300AP

Specifications

Boat Details

PricePOABoat BrandSuzukiModelDF300APLength0.00

Year 2020 Category Boat Engines and Outboards Hull Style Hull Type

Power Type Stock Number

New State New South Wales

Suburb MULGRAVE Engine Make Suzuki

Finance Available

Terms & Condition

Condition

This weekly repayment estimate is provided by Stratton Finance Pty Ltd (Australian Credit Licence No. 364340) ("Stratton"). Stratton is a finance broker. This repayment is calculated with an interest rate of % p.a. over a term of months. The interest rate is indicative of the rates on offer through Stratton's lending panel. The repayment estimate applies to the price shown. The price shown may not include other additional costs such as stamp duty, government fees and other charges payable in relation to the item. This estimate should be used for information purposes only and is not an offer of finance on particular terms. Credit fees, service fees and charges may apply. Credit to approved applicants only. A quote, details of all fees and charges may be obtained by contacting Stratton via stratton.com.au or calling 1300 955 600.



Phone: 02 4577 6699
Email: sales@blakesmarine.com.au
Website: https://www.blakesmarine.com.au
1 Railway Road North Mulgrave NSW 2756

From \$ p/w^. Please call 1300 787 288 for more information.

Description

DF300AP

Features

Multi-point sequential electronic fuel injection □□□Standard

Variable valve timing $\square\square\square$ Standard

Two-stage gear reduction system □□□Standard

Offset driveshaft <a>D Standard

Over-rev. limiter [[[]] Standard

Low oil pressure caution □□□Standard

Speedometer pickup on gear case □□□Standard

Suzuki anti-corrosion system □□□Standard

Suzuki Lean Burn Control system [[[]]Standard

Selective rotation □□□Standard

Suzuki precision control DDDStandard

Specifications

Shaft length □□□X: 635mm (25") | XX: 762mm (30")

Fuel delivery system [][]Multi-point sequential electronic fuel injection

No. of cylinders \[\] \[\] \V6 (55-degree)

Piston displacement \[\] \[\] \[4,028cm3

Bore x Stroke \[\] \[\] \[98mm x 89mm

Maximum output \[\] \[\] \[220.7kW

Full throttle operating range □□□5,700-6,300rpm

Steering DDRemote

Oil pan capacity □□□8.0 litres

Alternator □□□12V 54A

Engine mounting □□□Shear mount

Trim method $\square\square\square$ Power trim & tilt

Gear ratio □□□2.08:1
Gear shift □□□F-N-R

Exhaust DDThrough prop hub exhaust

Propeller selection (pitch) \[\] \[\] \[17"-27.5" (s/s)

Fuel [] minimum 95 (RON) octane

Warranty □□□5 years for recreational use

Engine Details

Engine Make Suzuki
Horse Power 300
Drive Type 8