







Suzuki DF325A

POA



Specifications

Boat Details

Price POA Boat Brand Suzuki Model DF325A Length 0.00

Year 2020 Category Boat Engines and Outboards

Hull StyleHull TypePower TypeStock NumberDF325A

Condition New State New South Wales

Suburb MULGRAVE Engine Make Suzuki

Finance Available

Terms & Condition

This weekly repayment estimate is provided by Stratton Finance Pty Ltd (Australian Credit Licence No. 364340) ("Stratton"). Stratton is a finance broker. This repayment is calculated with an interest rate of % p.a. over a term of months. The interest rate is indicative of the rates on offer through Stratton's lending panel. The repayment estimate applies to the price shown. The price shown may not include other additional costs such as stamp duty, government fees and other charges payable in relation to the item. This estimate should be used for information purposes only and is not an offer of finance on particular terms. Credit fees, service fees and charges may apply. Credit to approved applicants only. A quote, details of all fees and charges may be obtained by contacting Stratton via stratton.com.au or calling 1300 955 600.



Phone: 02 4577 6699
Email: sales@blakesmarine.com.au
Website: https://www.blakesmarine.com.au
1 Railway Road North Mulgrave NSW 2756

From \$ p/w^. Please call 1300 787 288 for more information.

Description

DF325A

Features

Start system [[]] Electric start

Multi-point sequential electronic fuel injection □□□Standard

Variable valve timing □□□Standard

Two-stage gear reduction system □□□Standard

Offset driveshaft [[[]]Standard

Over-rev. limiter \|\pi\p\Standard

Low oil pressure caution □□□Standard

Fresh water flushing system $\square\square\square$ Standard

Suzuki anti-corrosion system [[]]Standard

Dual water inlet □□□Standard

Suzuki Lean Burn Control System □□□Standard

Suzuki precision control [][]Standard

Maintenance-free timing chain □□□Standard

Power trim & tilt □□□Standard

Gear shift □□□F-N-R

Highly reliable lubrication system □□□Standard

Direct intake □□□Standard

Suzuki dual louver system $\square\square\square$ Standard

Dual injector □□□Standard

Suzuki dual prop system □□□Standard

Quiet operation □□□Standard

Knock sensor □□□Standard

Suzuki water detecting system ∏∏∏Standard

Specifications

Shaft length □□□X: 635mm (25") | XX: 762mm (30")

Fuel delivery system \[\] \[\] Multi-point sequential electronic fuel injection

No. of cylinders □□□V6 (55-degree)
Displacement □□□4,390cm3
Bore x Stroke □□□98mm x 97mm
Maximum output □□□239kW

Full throttle operating range □□□5,700–6,300rpm

Steering | Remote

Oil pan capacity □□□8.0 litres

Ignition system [[] Fully-transistorised

Alternator □□□12V 54A

Engine mounting □□□Shear mount

Trim method $\square\square\square$ Power trim & tilt

Gear ratio $\square \square \square 2.29:1$

Gear shift DDF-N-R (Drive by Wire)

Exhaust DDThrough prop hub exhaust

Propeller selection (pitch) $\square\square\square19.5$ "-31.5" (s/s)

Fuel [][]minimum 91 (RON) octane

Warranty □□□5 years for recreational use

Engine Details

Engine Make Suzuki
Horse Power 325
Drive Type 8